
Uniform Error Estimates for Finite Differences Methods Applied to Navier-Stokes Flow with Interfaces J. Thomas Beale Duke University

Finite differences with regular grids, irregular boundaries with jump conditions at the bdry or interface Re = O(1), viscosity improves errors immersed interface method rather than

immersed boundary method (sorry Charlie!)
Estimates in maximum norm for several equations
(1) Discrete Poisson equation, gain in regularity
(2) Discrete diffusion equation, gain with implicit time step
(3) Error estimates for Navier-Stokes with a moving interface, velocity and pressure, neglecting the error in interface position validating the general approach in a simple setting

The Problem and the Result

Navier-Stokes eq'ns in \mathbb{R}^2 or \mathbb{R}^3 periodic boundary conditions interface $\Gamma(t)$, a closed surface force **f** on Γ acts on fluid Re = O(1)Charlie's prototype problem



 $\frac{\partial \mathbf{u}}{\partial t} + \mathbf{u} \cdot \nabla \mathbf{u} = -\nabla p + \mu \Delta \mathbf{u} + \mathbf{f} \delta_{\Gamma}$ $\nabla \cdot \mathbf{u} = \mathbf{0}$

The interfacial force **f** amounts to jumps in ∇ **u** and *p*.

Result. We assume $\Gamma(t)$ known; f, $\nabla_{tan}f$ known to $O(h^2)$. With one scheme based on the immersed interface method, with truncation error O(h) at Γ and $O(h^2)$ elsewhere, the error in velocity and pressure is uniformly about $O(h^2)$. Estimates in maximum norm for finite difference versions of equations such as

$$\Delta u = f , \quad u_t = \Delta u + f$$

on a rectangular grid in \mathbb{R}^d , any dimension dEstimates in L^2 are the most natural. For problems with limited smoothness, e.g. with interfaces, largest error is typically on a small set L^∞ is a more meaningful measure of error than L^2 methods are designed to control maximum truncation error

We get estimates of the form $\Delta_h u^h = f^h \rightarrow ||u^h|| \leq C|f^h|$ Equations are linear, so that estimates apply to errors: If $\Delta_h u^h = f^h$ and $\Delta_h u^{exact} = f^h + \varepsilon^h$, $\varepsilon^h =$ truncation error, we subtract to get $\Delta_h (u^h - u^{exact}) = -\varepsilon^h$ and

$$\|u^h - u^{exact}\| \le C|\varepsilon^h|$$

Discrete Laplacian (d = 2) with spacing h: $\Delta_h u(ih, jh) = (u_{i+1,j} + u_{i-1,j} + u_{i,j+1} + u_{i,j-1} - 4u_{i,j}) / h^2$ $\Delta_h u = D_1^+ D_1^- u + D_2^+ D_2^- u$ $D_1^+ u = (u_{i+1,j} - u_{i,j}) / h, \quad D_1^- u = (u_{i,j} - u_{i-1,j}) / h$ For smooth u, $\Delta_h u = \Delta u + O(h^2)$ from Taylor expansion Does inverting Δ_h gain differences?

For the exact problem $\Delta u = f$, periodic, average zero we have sharp L^p estimates, 1

$$||D^k u||_{L^p} \le C_p ||f||_{L^p}, \qquad k \le 2$$

There are also "sharp" estimates in Hölder norms $C^{k+\lambda}$ (Schauder estimates) but **not** L^{∞} **Estimate for the Discrete Laplacian.** Suppose u_h and f_h are periodic grid functions on \mathbb{R}^d with average zero and $\Delta_h u_h = f_h$. Then in maximum norms

 $||u_h|| + ||D_h u_h|| \le C ||f_h||,$ $||D_h^2 u_h|| \le C |\log h|||f_h||$

with C independent of h, $D_h =$ any first difference. The log factor cannot be improved.


E.g.,
$$u(x, y) = (x^2 - y^2) \log r$$

This can be proved using estimates for a discrete Green's function.

J.T.B. and A. Layton, CAMCoS (2006) The discrete maximum principle estimates u_h , but not differences. V. Thomée proved discrete Schauder estimates (1968). Estimates for finite element spaces are better known.

Poisson problem with an interface


$$\begin{array}{lll} \Delta u_- \ = \ f_- & \mbox{in} \ \ \Omega_- \ , & \ \Delta u_+ \ = \ f_+ & \mbox{in} \ \ \Omega_+ \ , \\ [u] \ = \ g_0 & \mbox{on} \ \ \Gamma \ , & \ \ [\partial_n u] \ = \ g_1 & \mbox{on} \ \ \Gamma \end{array}$$



◆□ > ◆□ > ◆豆 > ◆豆 > ̄豆 = のへで

Poisson problem with an interface

$$\begin{aligned} \Delta u_- &= f_- \quad \text{in } \ \Omega_- \ , \quad \Delta u_+ &= f_+ \quad \text{in } \ \Omega_+ \ , \\ [u] &= g_0 \quad \text{on } \ \Gamma \ , \qquad [\partial_n u] &= g_1 \quad \text{on } \ \Gamma \end{aligned}$$



$$\begin{array}{l} \Delta_h u(ih) - \Delta u(ih) = O(h^2) \\ \text{at regular points,} \\ \text{away from } \Gamma \\ \Delta_h u(ih) - \Delta u(ih) \text{ is large} \\ \text{at irregular points,} \\ \text{where } \Delta_h \text{ crosses } \Gamma \end{array}$$

If we improve the truncation error to O(h) at the irreg. pts. using the Immersed Interface Method, then the error in u is uniformly $O(h^2)$, and the error in $D_h u$ is uniformly $O(h^2 |\log h|)$ Immersed Interface Method, R. LeVeque, Z. Li; A. Mayo Poisson problem with interface:

$$\begin{aligned} \Delta u_- &= f_- \quad \text{in } \ \Omega_- \ , \quad \Delta u_+ &= f_+ \quad \text{in } \ \Omega_+ \ , \\ [u] &= g_0 \quad \text{on } \ \Gamma \ , \qquad [\partial_n u] &= g_1 \quad \text{on } \ \Gamma \end{aligned}$$

Find C_h so that $\Delta_h u^{exact} - f^{exact} = C_h + O(h)$. Solve

$$\Delta_h u_h = f_h + C_h$$

 $C_h = 0$ at regular grid points; truncation error $O(h^2)$ $C_h \neq 0$ at irregular grid points near Γ , e.g. If $x_j \in \Omega_-$, $x_{j+1} \in \Omega_+$, $h_+ = x_{j+1} - x^*$

$$v_{xx}(x_j) = \frac{v_{j-1} - 2v_j + v_{j+1}}{h^2} - \frac{1}{h^2} \left([v] + h_+ [Dv] + \frac{h_+^2}{2} [D^2 v] \right) + O(h)$$

Zhilin Li & K. Ito, The Immersed Interface Method..., SIAM, 2006

With corrections, $\Delta_h(u_h - u) = O(h)$ at the irregular points since the C_h 's cancel. It is $O(h^2)$ at the regular points.

Theorem. With truncation error $O(h^2)$ at regular points and O(h) truncation error at irregular points,

$$|u_h(jh) - u(jh)| \le C_0 h^2$$
,
 $|D_h u_h(jh) - D_h u(jh)| \le C_1 h^2 |\log h|$.

Brief summary of proof (J.T.B. and A. Layton, CAMCoS '06): The O(h) truncation error at irregular points has the form

$$F_0 + D_h^{(1)}F_1 + \dots + D_h^{(d)}F_d, \qquad F_i = O(h^2)$$

Then $\Delta_h(u_h - u) = F_{reg} + F_0 + \nabla_h \cdot (F_1, \dots, F_d)$ The estimate for $u_h - u$, has a gain of one deriv for $D_h(u_h - u)$, gain of two derivs, log factor **Lemma.** Suppose f^{irr} is a grid function on Ω such that $f^{irr} \neq 0$ only at irregular points (near the interface). Then there are periodic grid functions F_k so that $f^{irr} = F_0 + \sum_{k=1}^d D_k^- F_k$ and

$$\|F_k\|_{max} \leq Ch\|f^{irr}\|_{max}.$$

Key example in one dimension: F(ih) = 0 for $i \le 0$; F(ih) = 1 for i > 0Set $D_h^+F(ih) = [F((i+1)h) - F(ih)]/h$ Then $D_h^+F(ih) = 1/h$ for i = 0; $D_h^+F(ih) = 0$ for $i \ne 0$ $D_h^+F \rightarrow F$ gains a factor of h in maximum norm.

To prove in dimension d, write f^{irr} locally as the difference of its sum in a direction transverse to Γ ; use partition of unity Similar lemmas in L^2 : Hackbusch '81, Stevenson '91

Gain in Regularity for Parabolic Difference Equations

Suppose we approximate (using backward Euler)

$$u_t = \Delta u + f, \quad u(\cdot, 0) = 0$$

by or with Then

$$u^{n+1} - u^n = \tau \Delta_h u^{n+1} + \tau f^{n+1}$$
$$u^{n+1} = (I - \tau \Delta_h)^{-1} (u^n + \tau f^{n+1})$$
$$t_n = n\tau, \ \tau = \text{ time step } = ch$$

$$\|u^{n}\| + \|D_{h}u^{n}\| \leq C_{1} \sup_{t \leq T} \|f(\cdot, t)\|$$
$$|D_{h}^{2}u^{n}\| \leq C_{2} (1 + |\log h|) \sup_{t \leq T} \|f(\cdot, t)\|$$

 Similar statements hold for a class of time-stepping methods...
 Interpretation: u^{computed} – u^{exact} and differences are bounded by maximum truncation error.
 J.T.B. "Smoothing properties...", SINUM 2009.

Gain in Regularity for Diffusive Difference Equations

Discretize $u_t = \Delta u$ in $\mathbb{R}^d \times [0, T]$ grid spacing h, time step τ use implicit time stepping, $\tau = O(h)$ for a single step method, $u^{n+1} = Su^n$ and $u^n = S^n u^0$ e.g., Crank-Nicolson method (second-order accurate): $u^{n+1} - u^n = (\tau/2)(\Delta_h u^{n+1} + \Delta_h u^n),$ $S = s(\tau \Delta_h) = (1 + \frac{\tau}{2}\Delta_h)(1 - \frac{\tau}{2}\Delta_h)^{-1}$

The best results are for *L*-stable methods. CN is A-stable, but **not** L-stable; $s(\infty) \neq 0$. A-stable means $|s(z)| \leq 1$ for Re $z \leq 0$ L-stable means A-stable and $s(z) \rightarrow 0$ as $z \rightarrow \infty$ Examples: backward Euler, TGA (an improvement of CN); one SDIRK2 (Runge-Kutta); BDF2 (but multi-step) Main Result. For an L-stable, single step method, or BDF2 with operator norm on $L^{\infty}(\mathbb{R}_{h}^{d})$,

$$\|S^n\| \le C_0$$

 $\|D_h S^n\| \le C_1 (n au)^{-1/2}$
 $\|D_h^2 S^n\| \le C_2 (n au)^{-1}$

for $n\tau \leq T$, with constants indep't of h, τ . For CN we get more limited estimates: $||S^n|| \leq C_0$ and

$$\|D_h RS^n\| \le C_1 (n\tau)^{-1/2}, \quad R = (1 - \frac{\tau}{2}\Delta_h)^{-1}$$

J.T.B., "Smoothing Properties...", SINUM, 2009

Related work: Aronson ('63), Widlund ('66) for $\tau = O(h^2)$; Ashyralyev & Sobolevskii; Thomée et al. for finite elements Michael Pruitt, Numer. Math. ('14) generalization to parabolic operators with variable coefficients

Discretizing the Navier-Stokes equations

For exact solutions with periodic boundary conditions

$$u_t + u \cdot \nabla u + \nabla p = \Delta u + F, \quad \nabla \cdot u = 0$$

Use P, the L^2 -projection on divergence-free vector fields

$$u_t + P(u \cdot \nabla u) = \Delta u + PF$$

where $Pw = w - \nabla \Delta^{-1} \nabla \cdot w$ To discretize in space, use centered diff's for ∇ , e.g.

$$\frac{\partial u}{\partial x_1} \approx \frac{u_{i+1,j} - u_{i-1,j}}{2h}$$

We use the usual discrete Laplacian and get an "approximate projection". (A staggered grid (MAC) would avoid this.) Use centered differences for grad and div, $\nabla \approx \nabla_h$ Suppose we define $\Delta_w u = \nabla_h \cdot \nabla_h u$, then Δ_w is the "the wide Laplacian", in 2D

$$\Delta_w u = \frac{u_{i+2,j} + u_{i-2,j} + u_{i,j+2} + u_{i,j-2}}{4h^2}$$

 $P_0 = I - \nabla_h \Delta_w^{-1} \nabla_h \cdot$ is a projection, i.e. $P_0^2 = P_0$, "the exact discrete projection" but it is preferable to use the usual discrete Laplacian,

$$\Delta_h u = \frac{u_{i+1,j} + u_{i-1,j} + u_{i,j+1} + u_{i,j-1}}{h^2}$$

Then we get an "approximate projection"

$$ilde{P} = I -
abla_h \Delta_h^{-1}
abla_h \cdot , \qquad ilde{P}^2
eq ilde{P}$$

Cf. Almgren, Bell, Crutchfield, 2000.

$$\tilde{P} = I - \nabla_h \Delta_h^{-1} \nabla_h \cdot =$$
 "approx projection"
 $P_0 = I - \nabla_h \Delta_w^{-1} \nabla_h \cdot =$ "exact discrete projection"

With periodic boundary conditions,

 $\Delta_h = 0$ on constants, invertible on fcns of mean value zero Δ_w has a null space with dim 2^d , = 0 on constants and $(-1)^j$.


(日) (同) (三) (三) (三) (○) (○)

On L^2 , $\|\tilde{P}\| \leq 1$, from checking eigenvalues (L^2 stability) On L^{∞} , $\|\tilde{P}\| \leq C |\log h|$, using the elliptic estimate. Similarly for P_0 ...

Often with interfaces a MAC (staggered) grid is used so that the approx proj'n is an exact proj'n.

Navier-Stokes with a moving interface

periodic bdry cond'ns on box interface Γ , depending on tforce f on Γ acts on fluid force on Γ amounts to jumps in p and ∇u (here in 2D)



$$\frac{\partial u}{\partial t} + u \cdot \nabla u = -\nabla p + \mu \Delta u + f \delta_{\Gamma}$$
$$\nabla \cdot u = 0$$
$$[\partial p] \qquad \partial$$

$$[p] = f \cdot n, \quad \left[\frac{\partial p}{\partial n}\right] = \frac{\partial}{\partial s} \left(f \cdot \tan\right),$$
$$[u] = 0, \quad \mu \left[\frac{\partial u}{\partial n}\right] = -\left(f \cdot \tan\right) \tan \theta.$$

The Scheme for Navier-Stokes
time step
$$\tau = O(h)$$
, viscosity = 1
 $u^{n+1} - u^n = -\tau (u \cdot \nabla u)^{n+1/2} - \tau \nabla p^{n+1/2} + \tau \Delta u^{n+1/2} + \tau C_1 + \tau C_7$
 C_1 corrects $u_t^{n+1/2} \approx (u^{n+1} - u^n)/\tau$ if crossing Γ
 $(u \cdot \nabla u)^{n+1/2} = \frac{3}{2}u^n \cdot \nabla_h u^n - \frac{1}{2}u^{n-1} \cdot \nabla_h u^{n-1} + C_2$
 $\Delta u^{n+1/2} = \frac{1}{2} (\Delta_h u^{n+1} + \Delta_h u^n) + C_3$
 C_2 and C_3 correct differences using jumps in Du , D^2u

$$\Delta_h p^{n+1/2} = -\left(\nabla_h \cdot (u \cdot \nabla u)^{n+1/2} + C_4\right) + C_5 - m$$

 C_5 uses jumps in p, $\partial p/\partial n$, $u \cdot \nabla u$ m is a constant so RHS has mean value zero

$$\nabla p^{n+1/2} = \nabla_h p^{n+1/2} + C_6$$

▲□▶ ▲□▶ ▲□▶ ▲□▶ ▲□ ● ● ●

This scheme is similar to ones that have been developed:

Z. Li, M.-C. Lai, JCP 2001 L. Lee, R. LeVeque, SISC 2003 D. Le, B. Khoo, J. Peraire, JCP 2006 S. Xu, Z. J. Wang, JCP 2006

We assume periodic boundary conditions in the computational box.With a solid boundary, the bdry cond'n must be discretized.Discretizing at the boundary and at the interface should be separate issues?Often a MAC grid is used; the analysis should apply.

Xu & Wang use explicit time stepping, larger Re. truncation error $O(h^2)$ at the interface needed for $O(h^2)$ solution error

Error Estimates, Statement of Result

Theorem. Assume the exact solution is good for $0 \le t \le T$. Neglect errors in the location of Γ . Assume f and $\nabla_{tan} f$ are known to $O(h^2)$.

Choose time step au with au/h fixed. Then for $t_n = n au \leq T$

$$\max_{j,n} \left| u^{computed}(x_j, t_n) - u^{exact}(x_j, t_n) \right| \leq K_T h^2 |\log h|^2$$

Similarly the pressure error is bounded by $h^2 |\log h|^3$ except for an indefinite constant.

Error Estimate for NSE

u, p computed quantities; v, q exact

$$v^{n+1}-v^n = -\tau (v \cdot \nabla v)^{n+1/2} - \tau \nabla q^{n+1/2} + \tau \Delta v^{n+1/2} + \tau C_1 + \tau C_7 - \tau \varepsilon^n$$

Here $q^{n+1/2}$ solves a Poisson problem like $p^{n+1/2}$, v in place of uFor example, the error in $\Delta v^{n+1/2}$ is

 $O(h^2)$ at regular points, O(h) at irregular points It has the form $O(h^2) + DO(h^2) = (I + D)O(h^2)$ by the Lemma We show the truncation error is

$$\varepsilon^n = (I+D)O(h^2|\log h|), \quad \varepsilon^0 = O(h|\log h|)$$

Let w = u - v = v elocity error; subtract equations, cancel C's ! Set $g^{n+1/2} \equiv (u \cdot \nabla_h u)^{n+1/2} - (v \cdot \nabla_h v)^{n+1/2}$. Then

$$\nabla_h p^{n+1/2} - \nabla_h q^{n+1/2} = -\nabla_h \Delta_h^{-1} \nabla_h \cdot g^{n+1/2} = -(I - \tilde{P}) g^{n+1/2}$$

$$w^{n+1} - w^n = -\tau \tilde{P}g^{n+1/2} + (\tau/2)(\Delta_h w^{n+1} + \Delta_h w^n) + \tau \varepsilon^n$$

(日) (同) (三) (三) (三) (○) (○)

Error Estimate for NSE, page 2 of 4

w = u - v = velocity error; $\tilde{P} =$ approx proj'n, $P_0 =$ exact proj'n

$$w^{n+1} - w^n = -\tau \tilde{P}g^{n+1/2} + (\tau/2)(\Delta_h w^{n+1} + \Delta_h w^n) + \tau \varepsilon'$$

$$R = (I - \frac{\tau}{2}\Delta_h)^{-1}, \quad S = (I + \frac{\tau}{2}\Delta_h)(I - \frac{\tau}{2}\Delta_h)^{-1}$$
$$w^{n+1} = Sw^n - \tau R\tilde{P}g^{n+1/2} + \tau R\varepsilon^n$$

Since $\|\tilde{P}\| \sim |\log h|$, a direct stability estimate doesn't work? Define $y^n = P_0 w^n$ and $z^n = (I - P_0) w^n$, and estimate separately. $\|w^n\| \leq \|y^n\| + \|z^n\|$ but not the reverse!

$$y^{n+1} = Sy^n - \tau RP_0 g^{n+1/2} + \tau P_0 R\varepsilon^n$$

$$z^{n+1} = Sz^n - \tau RA(I - P_0)g^{n+1/2} + \tau(I - P_0)R\varepsilon^n$$

(日) (同) (三) (三) (三) (○) (○)

where $A = (\Delta_h - \Delta_w)\Delta_h^{-1}$ is bounded indep't of *h* (proof uses the Fourier multiplier)

Error Estimate for NSE, page 3 of 4

$$y^{n+1} = Sy^n - \tau RP_0 g^{n+1/2} + \tau P_0 R\varepsilon^n$$

 $y^n = P_0 w^n$; $g^{n+1/2} = (u \cdot \nabla_h u)^{n+1/2} - (v \cdot \nabla_h v)^{n+1/2}$ We know g is bounded like $||D_h y|| + ||D_h z||$. We need to know the same for $P_0 g = g - \nabla_h \Delta_w^{-1} (\nabla_h \cdot g)$. How to avoid the log h from P_0 ?

 $g = v \cdot \nabla_h w + \dots = v \cdot \nabla_h y + v \cdot \nabla_h z + \dots$ For exact equations, $\nabla \cdot (v \cdot \nabla v) = \sum v_{j,i} v_{i,j}$ since $\nabla \cdot v = 0$. Here $y^n = P_0 w^n$, $\nabla_h \cdot y^n = 0$, and the same works. $z^n = (I - P_0) w^n$ is a discrete gradient, $D_{hi} z_j = D_{hj} z_i$ and $(I - P_0)(v \cdot \nabla_h z) = \nabla_h \Delta_w^{-1} \Delta_w (v_j z_j) + D_h B(z) = \nabla_h (v_j z_j) + D_h B(z)$ All together $P_0 g^{n+1/2} = \Phi_0^n + D_h \Phi_1^n + \text{ (same } (n-1))$ where $\|\Phi_k^n\| \le K(\|y^n\| + \|z^n\|), k = 0 \text{ or } 1$ It is important that v is continuous so that Dv is bounded!

Error Estimate for NSE, concluded

$$y^{n+1} = Sy^n - \tau RP_0 g^{n+1/2} + \tau P_0 R\varepsilon^n$$

$$y^{n+1} = -\tau \sum_{\ell=1}^n S^{n-\ell} RP_0 g^{\ell+1/2} + \tau \sum_{\ell=0}^n S^{n-\ell} RP_0 \varepsilon^\ell$$

We use $||S^{n-\ell}RD_h|| \sim ((n-\ell)\tau))^{-1/2}$, $P_0g \sim Dy + Dz$ Define $\delta^n = \max(||y^m|| + ||z^m||)$, $m \leq n$

$$| ext{first sum}| \, \sim \, \sum_{\ell=1}^{n-1} ((n-\ell) au))^{-1/2} \delta^\ell au + au^{-1/2} \delta^n au$$

Similarly for the second sum, with $\varepsilon^{\ell} \sim (I + D)O(h^2 |\log h|^2)$. Add a similar estimate for z^n to get $\delta^{n+1} \leq K_1 \sum_{\ell=1}^{n-1} ((n-\ell)\tau))^{-1/2} \delta^{\ell} \tau + K_1 \tau^{-1/2} \delta^n \tau + K_2 h^2 (\log h)^2$

and finally, with Hölder and Grönwall,

$$\delta^{n+1} \leq Kh^2 (\log h)^2$$

- J.T.B., "Uniform error estimates for Navier-Stokes flow with an exact moving boundary using the immersed interface method" SIAM J. Numer. Anal. 53 (2015), 2097-2111.
 also available at arXiv.org
- J.T.B. and A. Layton, "On the accuracy of finite difference methods for elliptic problems with interfaces", Commun. Appl. Math. Comput. Sci. 1 (2006)
- J.T.B., "Smoothing properties of implicit finite difference methods for a diffusion equation in maximum norm", SIAM J. Numer. Anal. 47 (2009)

Michael Pruitt, Numerische Mathematik 128 (2014) discrete diffusion eq'ns, variable coeff'ts Another project:

JTB, W. Ying, and J. R. Wilson, "A simple method for computing singular or nearly singular integrals on closed surfaces", to appear in Comm. Comput. Phys.; also available at arXiv.org

W. Ying and JTB, "A fast accurate boundary integral method for potentials on closely packed cells," CiCP 14 (2013)

S. Tlupova and JTB, "Nearly singular integrals in 3D stokes flow," CiCP 14 (2013)

JTB, "A grid-based boundary integral method for elliptic problems in three dimensions", SINUM 42 (2004)

JTB and M.-C. Lai, "A method for computing nearly singular integrals", SINUM 38 (2001)